Via Cavolto, 10 22040 Anzano del Parco (Co) Tel. +39 031 33521 Fax +39 031 3352138

P.Iva 03046230987



info@nuovadefim.com www.nuovadefim.com

# RECINTHA® STADIUM

This specially designed fence for sport location is made in welded mesh according to the UNI EN 13200 norm. RECINTHA® STADIUM is not just a robust and very sturdy fence, but also guarantees to the audience an excellent vision through. In order to offer a product able to respond the new sports projects characteristics, this system has been equipped with particularly elegant and nice posts. Available in three models: RS1 H = 2230 mm; RS2 H = 2430 mm; RS3 H = 2230 mm + 630 mm (cranked top) to comply to different sports facility areas standards.

# **TECHNICAL DETAILS**

# **Dimensions**

- > Mesh 50x200 mm
- > Twin horizontal wires Ø 8 mm, vertical wires Ø 6 mm

### Materials

> Steel S235 JR UNI EN 10025

### Coating

- > Painting with polyester resins
- > Hot dip galvanized to UNI EN ISO 1461

> RAL 6005 green, other RAL colours available on demand

#### Gates

> Safety gates built in compliance of the applicable laws on football fields and stadiums partitions.

# APPLICATIONS

- > Football field fence
- > Sport arenas
- > Athletics grounds
- > Sports facilities
- > Hippodrome
- > Car racetrack

## **PRODUCT SPECIFICATIONS**

RECINTHA® STADIUM fence is made of 50x200 mm electro-welded wire mesh panels, with double 8 mm horizontal wires and 6 mm vertical ones, mounted on Omega section posts profile, secured with stainless steel anti-theft bolts and cover plate, all in accordance with the Norm UNI EN 13200 (sports playgrounds partitions). Finish hot-dip galvanized and painting polyester powder coated.

Post centers distance: 2570 mm.

				Harris .
		++++++		THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS NAMED IN COLUMN TW
				1111111
	2 <del>21 1 1 1 1</del>			
_				
ᇤ				
0				
543				
0		+++++		
from 2230 to 2430 mm				
23				
n 2		<del>11</del> 1111111111111		
5				
Ψ.			Later Control of the	
	: :			
		+++++1111111111111111111111111111111111		
		444	Annual Property Control	III III Clari
				50 mm _
				1
			2508 mm	1 00
	. 3		<b>L</b> -	
				_
				[
			Ċ	шш 002
			6	₹
				Ø 6 mm
				4-1-1-1
	/			
	- 1			
	/			
	\			\
	,			<del></del>
			The state of the s	
see pages 62-63-66		Omega post 120x60x30 mm	Cranked top	Horizontal railing "U"
		120x60x30 mm		railing "U"













