

TALIA® VENTUS

Thanks to the specific profiles, this product brings together elegance and privacy. With its refined design and the capability to preserve privacy, TALIA® VENTUS represents a typical product of Italian tradition, where attention to detail is a guarantee of quality and beauty. TALIA® VENTUS, is the only louvered fencing system certified for wind load, a characteristic the latter, granted by the post and panel integration, making the system even quicker and easier to install.

TECHNICAL DETAILS

Dimensions

- > Mesh 46x132 mm
- > Horizontal Talia® profiles
- > Vertical round bars 4 mm

Coating

- > S235JR UNI EN 10025 Steel

Coating

- > Hot-dip galvanized according to UNI EN ISO 1461
- > Painting with polyester resins

Colors

- > RAL 6005 green, other RAL colors available on demand

Fixing system

- > TTGST M10x30 stainless steel security bolt

Posts

- > 80x8 mm flat bar posts for concrete anchoring

Gates

- > Single, double or sliding leaf gates


APPLICATIONS

- > Luxury housing
- > Technical areas
- > Public buildings

APPLICATIONS

TALIA® VENTUS fencing consists of modular monolithic panels, 46x132 mm mesh, special section horizontal profiles (centre distance 46 mm), 4 mm diameter round vertical joining bars (centre distance 132 mm). 80x8 mm flat bar posts welded at the ends, making up one single unit ready for installation, with pre-drilled holes to fix consecutive panels. Post centre distance: 1650-2000 mm.

Finish: painting with polyester resins on hot galvanized material according to UNI EN ISO 1461.



PANEL				POST		Post to be set in concrete		Post with base plate	
H	L	Weight		Section	Fixing points	L	Weight galv.	L	Weight galv.
mm	mm	Kg/ea	kg/m²	mm	n°	mm	Kg/ea	mm	Kg/ea
954	1650	36,9	23,5	80x8	3	1200	6,6	1001	6,2
954	2000	41,9	22,0	80x8	3	1200	6,6	1001	6,2
1596	1650	60,0	22,8	80x8	3	1850	10,2	1643	9,8
1596	2000	68,6	21,5	80x8	3	1850	10,2	1643	9,8
1963	1650	74,1	22,9	80x8	3	2300	12,7	2010	11,8
1963	2000	84,8	21,6	80x8	3	2300	12,7	2010	11,8

